

Trimethylhydroxyethyl ethylenediamine CAS 2212-32-0 PC CAT NP80

Overview:

Product Name: Trimethylhydroxyethyl ethylenediamine

Chinese name: N,N-dimethylaminoethyl-N'-methylaminoethanol; N,N,N'-trimethylaminoethylethanolamine; 2-(dimethylaminoethylmethylamino)ethanol

Alias: trimethylhydroxyethylethylenediamine, trimethylhydroxyethylethylenediamine, CAS 2212-32-0, 2-(dimethylaminoethylmethylamino) ethanol, Dabco T, Toyocat RX5, Jeffcat Z -110, Lupragen N400, PC CAT NP80

English name: N,N,N'- -trimethylaminoethylethanolamine;N,N-dimethylaminoethyl-N'-methylaminoethanol

Molecular formula: C₇H₁₈N₂O

Relative molecular mass: 146.2

CAS number: 2212-32-0

performance:

Trimethylhydroxyethyl ethylenediamine is a colorless to light yellow liquid, easily soluble in water;


Viscosity (25°C, mPa.s): 7

Density (25°C, g/cm³): 0.91

Water-soluble: soluble in water

Flash point (PMCC, °C): 89

Hydroxyl value (mgKOH/g): 387



use:

Trimethylhydroxyethyl ethylenediamine is a low odor reactive foaming catalyst.

Trimethylhydroxyethyl ethylenediamine is mainly used for polyether polyurethane flexible foam catalyst,

molded foam, semi-rigid foam and hard foam, especially recommended for automotive foam.

application:

Trimethylhydroxyethyl ethylenediamine is a non-emission amine catalyst used to promote the urea (isocyanate-water) reaction. Because it contains active hydroxyl groups, it is easy to react into the polymer matrix;

Trimethylhydroxyethylethylenediamine can be used in soft and hard polyurethane systems that require smooth reaction characteristics.

Storage and transportation:

Should be sealed and stored in a dry, cool and ventilated warehouse

package:

200KG/drum Storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent the water and other substances from mixing into the product and affecting its performance. Store in a cool, dry place, keep the container sealed and avoid contact with oxides. Do not breathe dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work, shower and change clothes. Store contaminated clothing separately and wash it before reuse. Maintain good hygiene habits.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E-Mail:	Hunter@newtopchem.com
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)
Website:	www.newtopchem.com

FAQ

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C ,You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.) or by air. Usually it will cost 3-5days that you can get the goods after delivery.For large quantity products, shipping by sea is worthwhile.It will cost days to weeks to come to your destination port, which depends on where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.